

#### Columbus JACK / Regent



"The Strength of Experience"

#### Recovery Systems





## Recovery Systems



 Tripod Jack Design For Stability with Separate Power Supply Console.







- Capacity Up to 110 Tons (99.8 tonnes)
- Minimum Height of 21 Inches (533 mm)
- Maximum Overall Height = Standard Tripod Requirements
- Capable of Leveling Aircraft
- Safe Operation Under All Condition






TRIPOD AIRCRAFT RECOVERY SYSTEM SPECIFICATIONS					
MODEL NUMBER	VERT CAP (Tons/m tonnes)	MIN HEIGHT (Inches/mm)	HYD LIFT (Inches/mm)	SCREW EXT (Inches/mm)	MAX EXT HEIGHT (Inches/mm)
9162-012	50.0	21.0	49.0	5.0	75.0
	45.4	533	1,245	127	1,905
9161-012	60.0	88.0	216.0	5.0	309.0
	54.4	2,235	5,486	127	7,849
9143-012	100.0	28.0	107.0	5.0	140.0
	90.7	711	2,718	127	3,556
9497-010	110.0	68.0	162.0	24.0	254.0
	99.8	1,727	4,115	610	6,452







Mechanical Screw Extension With Jack Adapter

Integral Spring-Loaded Locknuts
On Each Stage Operate
Automatically During Extension.

Independently Controlled Legs

Transportable By Either Towing or Forklift








Independently Operated Legs
Provide Controlled Lateral
Movement of Jack Point to
Reduce Side Load During
Aircraft Leveling







Available Jack Point Lateral Movement Increases As Jack Is Extended

Model 9497-010 Chart Shown





- Air Operated For Safety
- Independent Controls For Each Jack Leg
- One Person Can Operate All Three Legs Simultaneously
- Towable or Transportable by Forklift







### Independent Color Coded Controls

- Separate Pressure Gauge
- Separate Control Valve
- Separate Air Pump
- Separate Relief Valve
- Separate Hand Pump
- Separate Release Valve







Visual Fluid Level Indication

Centralized
Connections for
Hoses and Air Input





Hose Storage

**Tool Storage** 





#### Columbus JACK/Regent



"The Strength of Experience"



