



ColumbusJACK/Regent

"The Strength of Experience"

2 & 5 GALLON FLUID DISPENSING UNIT



CLOSED SYSTEM - Use Quick-Disconnect to fill container for less spills and environmental protection.

OPEN SYSTEM - Open fill cap to fill container.



Durable, yet lightweight, these Fluid Dispensing Units safely store, transport and dispense engine oil, hydraulic fluids or other service fluids. Fully tested, little maintenance is required, insuring years of dependable service.

STANDARD FEATURES

- ◆ **Translucent Container** — The natural colored polyethylene container makes fluid levels and colors easy to see.
- ◆ **Lightweight Durability** — The construction is light enough to handle easily, yet can withstand rugged abuse and extreme conditions.
- ◆ **Reduced Contamination Threat** — The fill cap is fitted with a standard filler breather, reducing the threat of contamination. Or order the unit as a closed system and eliminate contamination and spills.
- ◆ **Weepage Eliminated** — The system pump is double sealed to eliminate weepage and to keep possible contamination from entering.
- ◆ **Compatibility** — Fluid Transfer Units are delivered with carefully selected seals and hoses to ensure compatibility with fluids being transferred.
- ◆ **East to Read Signage** — Signage on the container is color coded per industry standards making fluid recognition easy at a glance.

AVAILABLE OPTIONAL FEATURES

- ◆ 10 Foot (2 Gal) / 25 Foot (5 Gal) Hose with 9/16-18, 37° Swivel
- ◆ Totalizing Meter
- ◆ In-Line Secondary Filter
- ◆ Pressure Gauge
- ◆ Closed System Kit



ColumbusJACK/Regent

"The Strength of Experience"

2 Gallon Fluid Dispensing Unit

SPECIFICATIONS

- ✓ Fluid Capacity 2 U.S. Gallons (7.6 L)
- ✓ Pressure Output 175 psig (79.38 kPa)
- ✓ Output per Stroke 7.2 Cubic In. *(120cc)
- ✓ Hose Length 7 ft. with 9/16-18, 37° Swivel
- ✓ Standard Filter 3 Micron Nominal
*(1/4 Pint / Stroke)

WEIGHTS and DIMENSIONS

- ✓ Net Weight (dry) 14 lbs. (6.4 kg.)
- ✓ Gross Weight 29 lbs. (13.2 kg.)
- ✓ Shipping Carton 18" x 14" x 12"

AVAILABLE OPTIONS

- ✓ 10 Foot Hose with 9/16-18, 37° Swivel
- ✓ Totalizing Meter
- ✓ Pressure Gauge
- ✓ In-line Secondary Filter
- ✓ Closed System Kit

FLUID TRANSFER UNITS

| OPEN | CLOSED | SIGN | SEALS |
|-----------|-----------|--------------|-------|
| 1055-8100 | 1056-8100 | 5606 | FKM |
| 1055-8200 | 1056-8200 | MOBIL 254 | FKM |
| 1055-8300 | 1056-8300 | ENGINE OIL | FKM |
| 1055-8400 | 1056-8400 | EXXON 2380 | FKM |
| 1055-8500 | 1056-8500 | MOBIL JET II | FKM |
| | | | |
| 1057-8100 | 1058-8100 | SKYDROL | EP |
| 1057-8200 | 1058-8200 | HYDRAULIC | EP |
| 1057-8300 | 1058-8300 | HY JET IV | EP |

5 Gallon Fluid Dispensing Unit

SPECIFICATIONS

- ✓ Fluid Capacity 5 U.S. Gallons (18.9 ltr)
- ✓ Pressure Output 175 psig (79.38 kPa)
- ✓ Output per Stroke 7.2 Cubic In. *(120cc)
- ✓ Hose Length 15 ft. with 9/16-18, 37° Swivel
- ✓ Standard Filter 3 Micron Nominal
*(1/4 Pint / Stroke)

WEIGHTS and DIMENSIONS

- ✓ Net Weight (dry) 37 lbs. (6.36 kg.)
- ✓ Gross Weight 74.5 lbs. (13.18 kg.)
- ✓ Shipping Carton 42-1/2" x 18-1/4" x 24-1/2"

AVAILABLE OPTIONS

- ✓ 25 Foot Hose with 9/16-18, 37° Swivel
- ✓ Totalizing Meter
- ✓ Pressure Gauge
- ✓ In-Line Secondary Filter
- ✓ Closed System Kit

FLUID TRANSFER UNITS

| OPEN | CLOSED | SIGN | SEALS |
|-----------|-----------|--------------|-------|
| 1059-8100 | 1060-8100 | 5606 | FKM |
| 1059-8200 | 1060-8200 | MOBIL 254 | FKM |
| 1059-8300 | 1060-8300 | ENGINE OIL | FKM |
| 1059-8400 | 1060-8400 | EXXON 2380 | FKM |
| 1059-8500 | 1060-8500 | MOBIL JET II | FKM |
| | | | |
| 1061-8100 | 1062-8100 | SKYDROL | EP |
| 1061-8200 | 1062-8200 | HYDRAULIC | EP |
| 1061-8300 | 1062-8300 | HY JET IV | EP |

DO NOT MIX FLUIDS